

32 Normal RTU Version

LI #	Qty	Part Number	Description
1	32	SC 6AG12151AG404XB0	SIPLUS S7-1200 CPU 1215C DC/DC/DC with conformal coating based on 6ES7215-1AG40-0XB0 . compact CPU. DC/DC/DC. 2 PROFINET ports. onboard I/O 14 DI 24 V DC 10 DO 24 V DC 0.5 A 2 AI 0-10 V DC. 2 AO 0-20 mA DC. Power supply DC 20.4-28.8V DC. Program/data m...
			<i>*Mfr: SIEMENS *Mfr pn: 6AG12151AG404XB0 *UPC: 804766543463</i>
2	32	SC 6ES79548LC030AA0	SIMATIC S7. memory card for S7-1x 00 CPU/SINAMICS. 3. 3 V Flash. 4 MB
			<i>*Mfr: SIEMENS *Mfr pn: 6ES79548LC030AA0 *UPC: 4047623409052</i>
3	32	SC 6AG12211BH324XB0	SIPLUS S7-1200 SM1221 16DI, WITH CONFORMAL COATING BASED ON 6ES7221-1BH32-0XB0 . 16 DI, 24V DC, SINK/SOURCE,
			<i>*Mfr: SIEMENS *Mfr pn: 6AG12211BH324XB0 *UPC: 887621778866</i>
4	32	SC 6AG12314HD324XB0	SIPLUS S7-1200 SM231 4AI 12BIT FOR MEDIAL STRESS WITH CONFORMAL COATING BASED ON 6ES7231-4HD30-0XB0 . ANALOG INPUT, 4 AI, +/-10V, +/-5V, +/-2.5V, OR 0-20 MA 12 BIT + SIGN BIT (13 BIT ADC)
			<i>Mfr: SIEMENS *Mfr pn: 6AG1231-4HD32-4XB0 *UPC: 887621575991</i>
5	32	SC 6AG12411AH324XB0	SIPLUS S7-1200cm 1241. with conformal coating based on 6ES7241-1AH32-0XB0 . Communication module RS232. 9-pole D-sub (pin). supports Freeport
			<i>*Mfr: SIEMENS *Mfr pn: 6AG12411AH324XB0 *UPC: 804766543470</i>
6	32	SC 6AG11343AB007AY2	SIPLUS PS UPS1600 10A PN -25 ... +70 degree C with conformal coating BasedOn 6EP4134-3AB00-2AY0 . uninterruptible power supply with Ethernet/ POFINET interface Input 24 V DC Output 24 V DC/10 A
			<i>*Mfr: SIEMENS *Mfr pn: 6AG11343AB007AY2 *UPC: 804766536694</i>
7	128	SC 6AG19011BB107AA0	SIPLUS NET RJ45 PLUG 180 2X2
			<i>*Mfr: SIEMENS *Mfr pn: 6AG19011BB107AA0 *UPC: 887621174736</i>

17 RTU's Pony Pump Version

LI #	Qty	Part Number	Description
1	17	SC 6AG12151AG404XB0	SIPLUS S7-1200 CPU 1215C DC/DC/DC with conformal coating based on 6ES7215-1AG40-0XB0 . compact CPU. DC/DC/DC. 2 PROFINET ports. onboard I/O 14 DI 24 V DC 10 DO 24 V DC 0.5 A 2 AI 0-10 V DC. 2 AO 0-20 mA DC. Power supply DC 20.4-28.8V DC. Program/data m...
			<i>*Mfr: SIEMENS *Mfr pn: 6AG12151AG404XB0 *UPC: 804766543463</i>
2	17	SC 6ES79548LC030AA0	SIMATIC S7. memory card for S7-1x 00 CPU/SINAMICS. 3. 3 V Flash. 4 MB
			<i>*Mfr: SIEMENS *Mfr pn: 6ES79548LC030AA0 *UPC: 4047623409052</i>
3	17	SC 6AG12211BH324XB0	SIPLUS S7-1200 SM1221 16DI, WITH CONFORMAL COATING BASED ON 6ES7221-1BH32-0XB0 . 16 DI, 24V DC, SINK/SOURCE,
			<i>*Mfr: SIEMENS *Mfr pn: 6AG12211BH324XB0 *UPC: 887621778866</i>
4	17	SC 6AG12314HD324XB0	SIPLUS S7-1200 SM231 4AI 12BIT FOR MEDIAL STRESS WITH CONFORMAL COATING BASED ON 6ES7231-4HD30-0XB0 . ANALOG INPUT, 4 AI, +/-10V, +/-5V, +/-2.5V, OR 0-20 MA 12 BIT + SIGN BIT (13 BIT ADC)
			<i>Mfr: SIEMENS *Mfr pn: 6AG1231-4HD32-4XB0 *UPC: 887621575991</i>
5	17	SC 6AG12411AH324XB0	SIPLUS S7-1200cm 1241. with conformal coating based on 6ES7241-1AH32-0XB0 . Communication module RS232. 9-pole D-sub (pin). supports Freeport
			<i>*Mfr: SIEMENS *Mfr pn: 6AG12411AH324XB0 *UPC: 804766543470</i>
6	68	SC 6AG19011BB107AA0	SIPLUS NET RJ45 PLUG 180 2X2
			<i>*Mfr: SIEMENS *Mfr pn: 6AG19011BB107AA0 *UPC: 887621174736</i>
7	17	CD5.243	DC/DC Converter, 96W, 9-14VDC In, 23-28VDC Out, 4.2-3.4A
8	17	UF40.241	Buffer Module, 24-28VDC, 40A - Dimension
9	17	YRM2.DIODE	Redundancy Module, 24-60VDC, 20A, Dual Input with Monitor
10	17	3035691	COMPONENT TERMINAL, DIODE
11	17	3034426	End Cover
12	17	DS220S-12DC	12VDC Power Surge Protector THIS REPL CAT DS210-12DC