# 501 - AS-BUILT DRAWINGS

## I. GENERAL REQUIREMENTS

## I.1. REQUIREMENTS

As-Builts or record drawings are required for all JEA owned potable water, wastewater, chilled water and reclaimed water pipelines, pump stations, treatment plants and facilities located in either public right-of-way, in a dedicated JEA easement or on JEA property and shall be prepared in conformance with Section 501. All private (excluding single family residential) water, wastewater and reclaimed water pipelines and facilities are required to be as-built; however, the as-builts of the private facilities do not have to meet the same requirements outlined in Section 501. The following definitions shall apply to this section:

## I.2. DEFINITIONS

## 1.2.1. **AS-BUILT(S)**

- I.2.1.1. Applies to Work involving new construction or replacement construction and/or requires a Permit for Construction.
- I.2.1.2. They are a revised set of drawings that represent and document the final materials and location of installed Work. They reflect all changes made by Addendum, change order, or Supplemental Work Allowance (SWA) during the construction process, and show the exact dimensions, geometry, and location of all elements of the Work completed by a Contractor under a contract.
- I.2.1.3. They are submitted by the Contractor and certified by a Professional Land Surveyor in the employ of the Contractor or by a Professional Engineer in the employ of the Contractor upon completion of a project or of a phase of a project.

## 1.2.2. RECORD DRAWING(S)

- I.2.2.1. Applies to Work involving maintenance and/or minor replacement of existing infrastructure which does not require any Permit for Construction.
- I.2.2.2. They are a revised set of drawings that represent and document the final materials and location of installed Work. They show the exact dimensions, geometry, and location of all elements of the Work.
- I.2.2.3. These drawings do not require certification by a Professional Land Surveyor or Professional Engineer.

## 1.2.3. **REDLINE DRAWING(S)**

I.2.3.1. Applies to Work that is ongoing and documents the current installation progress of planned Work or applies to field observations and/or findings that represent a deviation, discovery, or change from expected conditions.

- **I.2.3.2**. These drawings do not require the certification by a Professional Land Surveyor or Professional Engineer.
- **1.2.3.3.** They represent and document the current materials and location of installed work.

### I.3. SUBMITTAL TIMING

Upon completion of the Work and prior to dedication of utilities to JEA or final payment under the Contract with JEA, Contractor shall furnish to JEA electronic copies of asset data tables and as-built drawings or record drawings which have been revised to indicate final as-built data (true to scale) and in accordance with all addenda, change orders, verbal field changes, JEA directives, Supplemental Work Account (SWA)s, and all requirements with respect to the drawings specified herein. A JEA representative shall verify as-built information is consistent with observable field conditions. Redrawn as-builts will be deemed unacceptable.

## I.4. JEA PROJECT WORK

- **I.4.1.** An electronic file of the original Project drawings will be furnished to Contractor for the purpose of recording and preparing as-built or record drawings.
- **1.4.2.** The Contractor shall provide access to buried facilities to allow for accurate horizontal and vertical measurements to be acquired by the surveyor or engineer as needed. Should discrepancies exist, at the discretion of JEA, and at no cost to JEA, the contractor shall verify buried facilities.
- I.4.3. All as-built information shall be recorded and kept current during the progress of the Work. Monthly, the Contractor or Developer's authorized agent shall furnish to the JEA Representative a copy "redline" set of drawings identifying those field changes made to the Work to date, along with a copy of the associated field notes. Revisions and recording of information on the "redline" copy set of drawings shall be done to scale, in red ink, clearly and accurately identifying those changes to the Work. The JEA Representative may review and comment on the drawings which shall be incorporated into the next month's as-built submittal. Failure to incorporate changes in the following month submittal may result in rejection of any invoice submittal to JEA, denial of certification of completion or denial of acceptance by JEA.
- **I.4.4.** The JEA representative will review and comment on the proposed final as-built drawings. The subsequent submittal shall incorporate a copy set of CADD drawing preliminary as-builts with comments by JEA. The JEA Representative shall review and comment on the copy set of CADD drawings which shall be incorporated into the final as-built submittal.

## I.5. SIGNED DOCUMENTS

### I.5.1. AS BUILT DRAWINGS

Each page of the as-built drawings shall bear the printed name, and the signed as-built certification of the general contractor, and the signed and sealed as-built certification of the professional surveyor and mapper (PSM) or registered professional engineer (PE) who provided the horizontal and vertical dimensions and elevations on the as-built drawing. The signatures shall certify that the as-built drawings do, in fact, reflect the true as-built conditions as located under the direct supervision of the registered surveyor and/or professional engineer. The drawings shall be certified using the forms provided by JEA (See the end of this section).

### 1.5.2. REDLINE DRAWINGS

Each page of the reline drawings shall bear the printed name, and the signed redline certification of the project manager who provided the horizontal and vertical dimensions and elevations on the as-built drawing. The signature shall certify that the re-line drawings do, in fact, reflect the true built conditions of the infrastructure. The drawings shall be certified using the forms provided by JEA (See the end of this section).

## I.6. FINAL SUBMITTALS

Upon completion of the work, Contractor shall deliver the following completed documents:

- **I.6.1.** As-Builts required for all projects requiring permitting:
  - 1.6.1.1. As-built drawings in .dwg format (Auto CAD) including all xref files
  - **I.6.1.2.** As-built drawings in PDF format
  - **1.6.1.3**. As-built submittal check lists, signed and completely filled out
  - I.6.1.4. As-built submittal transmittal form
  - **1.6.1.5.** Asset data tables for each asset type in JEA electronic format
- **I.6.2.** Record Drawings required for all minor maintenance work, water plants, wastewater plants, potable water wells, and reclaimed facilities that do not require permitting:
  - 1.6.2.1. Record drawings in .dwg format (Auto CAD) including all xref files
  - **I.6.2.2.** Record drawings in PDF format
  - I.6.2.3. Record drawing submittal check lists
  - I.6.2.4. Record drawing submittal transmittal form
  - I.6.2.5. Equipment attribute forms or Asset data tables for each asset type in JEA electronic format
- I.6.3. JEA will review the submittal for correctness and completeness and will return either an approval stamp or list of required changes for resubmission. Resubmittal of final drawings, with completed revisions, shall be accompanied by the marked-up set of revision requirements as provided by JEA.

## II. DRAWING REQUIREMENTS

When making changes to the AutoCAD drawing for as-built purposes, originally designed utility lines that were installed differently in the field shall be deleted with the applicable notes and the correct location, notes and coordinates should be drawn in and/or added in to accurately portray the as-built conditions. Simply changing the coordinates, notes or just adding notes is not acceptable. Do not strike through notes or elevation call-outs, change them in the drawing to reflect as-built conditions. Lines, notations or required information not affected by addenda or SWAs shall not be disturbed. The legend used on the original Project drawings shall also be used to make all necessary corrections.

- II.1.1. Each document shall be labeled "AS-BUILT" or "RECORD DRAWING", as applicable, in approximately 1" high letters and shall be submitted on 24" X 36" PDF sheets.
- II.1.2. Each document shall contain a graphic scale accurately representing the scale of the drawings.
- II.1.3. Each document shall contain a north arrow.
- II.1.4. As-builts shall utilize the State Plane Coordinate System using the Florida East Zone and the North American Datum of 1983 preferred for horizontal data; North American Vertical Datum (NAVD) 1988 Datum is preferred for elevation data. Benchmarks used must be shown and verified on the drawings.
- II.1.5. Deflections that result in a change of more than two feet from the designed alignment shall be located and recorded regardless of the presence of a fitting.
- II.1.6. To enable the efficient future location of the referenced facilities, the PSM or PE performing the as-built will independently verify the positional accuracy relative to the referenced horizontal and vertical datum. This will be accomplished through checks to published horizontal and vertical control points from local, state or federal agencies. These checks are to be independent of checks to local project control.
- II.1.7. The positional accuracy relative to the referenced published control points used shall not exceed 0.5' horizontally and 0.1' vertically. Elevations relative to the site facilities must be within 0.1' of each other.
- II.1.8. As-builts shall show physical dimensioning of the separation between water mains, sewer mains, reclaimed mains and chilled water mains at crossings with all water mains, wastewater mains and facilities, reclaimed mains, chilled water mains and storms drains and facilities. This can be shown by providing elevations of each pipe or structure, or noting measurement taken at the conflict crossing between the pipes or structures on the plan view. As-builts shall also show measurement of vertical and horizontal separation in areas where water mains are parallel to wastewater mains, reclaimed mains or storm drains. The vertical and horizontal separation shall be shown for the full length of the parallel run.
- **II.1.9.** Special detail drawings will be required where needed for clarity. Clarity is defined as pipe, fittings, valves, meter boxes, etc. clearly visible when printed to scale and when zoomed and viewed electronically.
- II.1.10. Vicinity map shall be included and be similar to a Google Map or Bing Map with an arrow pointing to the location of the project. Vicinity map shall not have aerial imaging. Vicinity map shall include major street names in bold allowing the project to be located quickly. Vicinity map on the cover sheet should be approximately 6 inches by 8 inches. Outside of the map write "Project Location" and a leader line pointing to the site.
- II.1.11. Master Plan phase maps required for projects that are built in phases, the phase included in the as-built shall be shown as related to previous and future phases (as applicable). Phase maps shall be shown the cover page an on each document.
- II.1.12. Street names

- II.1.13. Match lines referencing the appropriate drawing page sheet number.
- II.1.14. All easements shall be shown with Official Record (OR) Deed book and page. Contractor shall coordinate with JEA real estate for JEA acquired easements.
- II.1.15. Unless approved otherwise by JEA, the minimum scale requirements on the drawings are as follows:

• Pump Station Site: 1" = 5' (horizontal scale)

• Plan & Profile: 1" = 40' (20' preferred, horizontal scale)

1" = 4' (2' preferred, vertical scale)

• Plan (only): 1" = 40' (20' preferred, horizontal scale)

- II.1.16. Separate drawings are required for water, wastewater, reclaimed and chilled water. No drawings will be accepted which contain a combination of the above construction types, unless otherwise approved by JEA Manager. Exceptions will be allowed for simple single service, small property improvements where all utilities can be clearly depicted on one sheet.
- II.1.17. All features depicted in the as-built drawings must be surveyed, JEA will spot check all coordinates to ensure accuracy.
- II.1.18. Failure to comply with the JEA Standards herein or failure to verify "As Builts" as required shall result in the Contractor, Engineer, and/or Surveyor being restricted from bidding on future JEA projects and being removed from the JEA approved engineer, surveyor or contractor's list for a minimum of twelve months.
- II.1.19. Cover sheet shall include an "AS-BUILT" notice in Bold font approximately 1 inch tall, located at the top center of the sheet with the full Project Name provided underneath and Address (if applicable). The Vicinity Map is to be placed in the center of the cover sheet. (Reference V.1.10 for the Vicinity Map requirements). The Cover sheet and each As-Built sheet shall include the JEA Availability Number and/or the JEA Capital Project Number for each commodity Water, Wastewater, Reclaimed Water, and Chilled Water. These numbers shall be approximately .3 inches tall. A JEA representative will provide the JEA Capital Project Numbers at the preconstruction meeting and will be responsible for checking this information at the end of the project, when preliminary as-builts are submitted, to ensure that the JEA Capital Project Numbers have not been modified/added throughout the project. The Cover sheet and each As-Built sheet will also include the Certifications to be filled out, digitally signed, and sealed by the surveyor/mapper. The Cover sheet will also include the Legend, Surveyor Notes, the datum & reference to state plane coordinates (Florida East Zone NAD 83, NAVD 88), general notes (any specific utility notes are to be provided on the utility sheets), the date of utility installation completion, and a Title block.
- II.1.20. A call out shall be provided identifying the points of connection of the new project to the existing JEA infrastructure.

## **III. SPECIFIC SYSTEM REQUIREMENTS**

### III.1. PRESSURE PIPE SYSTEMS

This section covers pressure pipes including water, wastewater, reclaimed, vacuum and chilled.

- III.1.1. The location of all piping, valves, fittings, fire hydrants, meter boxes, backflow preventers, manholes, vacuum pods, casings, private pump outs, and points of connection to the existing system shall be referenced by coordinates.
- III.1.2. The positional accuracy relative to the referenced published control points used shall not exceed 0.5' horizontally and 0.1' vertically. Elevations relative to the site facilities must be within 0.1' of each other.
- III.1.3. Coordinates and elevations on the main and finished grade will be required at all pipe dead ends, size changes, points of connection to existing system, fittings, valves, meter boxes, at intersections/crossings of pipes, and at 100' maximum intervals from the nearest pipe or fitting elevation.
- III.1.4. Asset data tables are required for all valves, hydrants, meter boxes, manholes, vaults, vacuum pods, locate wire boxes, fittings, points along pipe (point of connection and top of pipe elevations), and pipe crossings. Private pump out assembly components are required to be included in the appropriate tables, see end of section for data table examples. (Data tables can be downloaded from jea.com.)
- III.1.5. Every valve, hydrant, meter box, manhole, vault, vacuum pod, locate wire box, private pump out assembly component, fitting, points along pipe, and pipe crossing on the as-built is to be numbered and referenced in the asset data table. Minimum font on data tables shall be 8 pts.

# **III.2. GRAVITY WASTEWATER SEWER SYSTEMS**

- III.2.1. The location of all piping, casings, wyes, tees, manholes, cleanouts and service points to the existing system shall be referenced by coordinates.
- III.2.2. The positional accuracy relative to the referenced published control points used shall not exceed 0.5' horizontally and 0.1' vertically. Elevations relative to the site facilities must be within 0.1' of each other.
- III.2.3. Runs of gravity sewer shall be identified (i.e., 300' of 8" PVC SDR26 at S=.004.) A run is defined as a pipe line between manholes.
- III.2.4. Service points shall be identified. A service point is defined as the lateral service point located at the transition from the public right of way or utility easement to private property at the property line. It is the point where JEA ownership ends and private ownership begins.
- III.2.5. Top of pipe elevations and finished grade elevations at the property line shall be given for all service points.
- III.2.6. Elevations shall be given for the north rim of the top of all manhole covers and all manhole inverts with the direction of the invert listed (N, E, S, W, NW, etc).
- III.2.7. Asset data tables are required for all gravity sewer runs, fittings on runs, service points and manholes. (See end of section for data table examples. Data tables can be downloaded from jea.com.)

III.2.8. Every gravity sewer run fitting, service point, and manhole on the as-built shall be numbered and referenced in the asset data table. Minimum font on data tables shall be 8 pts.

## III.3. WATER, RECLAIMED AND WASTEWATER PUMP STATIONS

- III.3.1. Wet well size and location shall be indicated and located relative to property lines and/or right-of-way lines.
- III.3.2. All utilities within the pump station site shall be located relative to property lines and/or right-of-way lines.
- III.3.3. The Contractor shall provide a boundary survey of the pump station site showing above and below ground improvements. This survey and sketch shall be prepared by a registered land surveyor in accordance with Chapter 472 of the Florida Statutes. The sketch shall be submitted with as-built drawings prior to pump station pre-start. The survey and sketch shall include:
  - III.3.3.1. Elevations shall be indicated at inverts, wet well top (rim elevation), wet well bottom, concrete slab corners and underground piping, valves and fittings.
  - III.3.3.2. All utilities materials and sizes of lines and fittings above and below ground shall be indicated.
  - III.3.3.3. As-built information shall be provided for the pump station site plan on a separate page. Within the pump station site plan/boundaries the following shall be located/drawn horizontally: all electrical panels (demarcation, control, distribution, meter can, disconnect/transfer switch(s), I/O and flow meter), emergency pump-outs, hose station, above and underground electrical conduit, piping, valves, ARVs, fittings, manholes, generator/pony pump and fuel tank (if applicable), transformer, irrigation system, fence, auxiliary electrical enclosures and flow meter as applicable.
- III.3.4. All schedules that show site information, wet well dimensions/data, pump/motor and electrical data and emergency pony pump/generator data shall be corrected to show the as-built condition and submitted with the pump station drawings.
- III.3.5. All buried electrical conduit shall be shown, with size indicated, including electrical service from utility transformer to station meter and to control panel.
- III.3.6. See Chapter IV. 2. Section 433 for additional requirements.
- III.3.7. The Contractor shall submit "As-built" drawings prior to pump station pre-start-up.
- III.3.8. See Pump Station As-Built check list at end of chapter.

## III.4. STORM DRAIN SYSTEMS

- III.4.1. The location of all piping, manholes, and inlets, shall be referenced by coordinates.
- III.4.2. The positional accuracy relative to the referenced published control points used shall not exceed 0.5' horizontally and 0.1' vertically. Elevations relative to the site facilities must be within 0.1' of each other.

- III.4.3. Runs of storm wastewaters shall be identified (i.e., 300' of 15" RCP at S=.004.)
- III.4.4. Elevations shall be given for the north rim of the top of all manhole covers and inlets and catch basins and all manhole, inlet and catch basin inverts.
- III.4.5. Storm Drain, manhole, inlet and catch basin types shall be identified.

## III.5. BUILDINGS AND INTERIOR EQUIPMENT

- III.5.1. As-built drawings for buildings shall be marked to indicate any and all changes made. As-built drawings shall also include the installed size, elevation and location of all interior equipment, structures and concealed materials, including plumbing, electrical conduits, ducts, air and piping. The piping shall be identified as to its use. Internal backflow devices shall be clearly noted in drawings.
- III.5.2. All equipment shall have equipment attribute forms for each asset type completed.

## III.6. HORIZONTAL DIRECTIONAL DRILL (HDD)

The beginning and ending points of the HDD main shall be provided by a registered Professional Surveyor and Mapper. The HDD contractor shall provide a JEA approved certified as-built drawing, directional bore log plan and profile on a 24 x 36 sheet and Auto CAD file (certified by the HDD contractor) of the HDD work indicating horizontal and vertical location data (continuous or data points not to exceed 25 LF of main). A copy of the bore log shall be placed on the correct "As-built" sheet where drills are performed. An electronic PDF file containing this same information shall also be provided. See Chapter VI. 2. - Section 750 for additional requirements.

## IV. ASSET SPECIFIC REQUIREMENTS

### IV.1. PIPELINES

- IV.1.1. Each pipe segment shall show a call out designating each length, size, material and pressure class of pipe installed with leader pointing to the installed pipe. Short pipe segments (less than 20 feet long) contained between fittings/valves can have the pipe length description and leader line grouped in one descriptive note with leader line pointing to the group of pipes/fittings/valves. The pipe lining manufacturer and material shall be noted, if applicable.
- **IV.1.2.** Pipe segments shall be defined as pipe lengths between valves, fittings, manholes, meter boxes, vacuum pods, pump stations, vaults, etc.
- **IV.1.3.** Lateral or service pipe segments shall be identified by a note on each page. Note shall describe the typical lateral/service size, pipe material, and pipe pressure class. Laterals/Services that deviate from the typical note shall have a pipe segment call out as described IV.1.1.
- IV.1.4. Gravity wastewater pipe segments shall be designated in a table, inserted in a conspicuous location within the As-Built, with the following data. Minimum font on as-built data tables shall be 8 pts.
  - Sewer Pipe Run Number (GM#)
  - Sewer Pipe Subtype = Collection, Trunk
  - Facility Owner (JEA or PRIVATE)

- Pipe Size (Inches)
- Pipe Class (SDR26, etc)
- Pipe Manufacturer
- Pipe Material (PVC, etc.)
- Pipe Lining Manufacturer
- Pipe Lining Material
- Pipe Length (feet)
- Downstream Pipe Invert Elevation (feet)
- Downstream Grade Elevation at Invert (feet)
- Upstream Pipe Invert Elevation (feet)
- Upstream Grade Elevation at Invert (feet)
- Slope (percent)
- **IV.1.5.** Gravity wastewater pipe table shall also be submitted in excel format using the JEA standard excel file which can be downloaded from jea.com. See end of section for data table examples.
- IV.1.6. Locations where the pipe is exposed aboveground, the beginning and ending points of the aboveground pipe shall be shown in the Points Along Pipe table, with Pipe Orientation noted as Aboveground.
- IV.1.7. Points along Pipe locations at points of connection and 100' maximum intervals on pressurized pipes shall be designated in a table, inserted in a conspicuous location within the As-Built, with the following data. Minimum font on as-built data tables shall be 8 pts.
  - Pipe Location Number (WPOC#, WWPOC#, RPOC#, WWPOL#, etc)
  - Pipe Location (Point of Connection, Top of Pipe, Top of Casing)
  - Pipe Subtype
  - Facility Owner
  - Pipe Size
  - Pipe Orientation (Underground/Aboveground)
  - Pipe Class
  - Pipe Manufacturer
  - Pipe Material
  - Pipe Lining Manufacturer
  - Pipe Lining Material
  - Finished Grade Elevation (feet)
  - Pipe Top Elevation (feet)
  - Pipe Cover (feet)
  - X Coord (State Plane Easting feet)
  - Y Coord (State Plane Northing feet)
  - Latitude (Decimal Degrees)
  - Longitude (Decimal Degrees)

- IV.1.8. Points along Pipe tables shall also be submitted in excel format using the JEA standard excel file which can be downloaded from jea.com. See end of section for data table examples.
- IV.1.9. Each top of pipe location shall show a call out on the plan view designating the top of pipe number that corresponds with the points along pipe table.
- IV.1.10. Points of conflicting utility crossings shall be designated in a table, inserted in a conspicuous location within the As-Built, with the following data. Minimum font on as-built data tables shall be 8 pts.
  - Crossing Number
  - Upper Pipe Type
  - Upper Pipe Size (inches)
  - Finished Grade Elevation (feet)
  - Upper Pipe Top Elevation (feet)
  - Cover to Top of Upper Pipe (feet)
  - Upper Pipe Bottom Elevation (feet)
  - Lower Pipe Type
  - Lower Pipe Size (inches)
  - Lower Pipe Top Elevation (feet)
  - Cover to Top of Lower Pipe (feet)
  - Separation Between Pipes (feet)
  - X Coord (State Plane Easting feet)
  - Y Coord (State Plane Northing feet)
  - Latitude (Decimal Degrees)
  - Longitude (Decimal Degrees)
- IV.1.11. Pipe Crossing tables shall also be submitted in excel format using the JEA standard excel file which can be downloaded from jea.com. See end of section for data table examples.
- IV.1.12. Each pipe crossing location shall show a call out on the plan view designating the crossing number, conflicting pipe types, and the separation between pipes in feet.

### IV.2. FITTINGS

- IV.2.1. Each fitting shall show a call out designating fitting number, fitting type (45, tee, etc.) and size with leader pointing to the installed fitting. All fittings must be clearly shown on the main. Multiple fittings in close proximity can be grouped with one leader line. A blow-up section may be required to accurately depict all fittings in a congested area.
- IV.2.2. Fittings shall be designated in a fitting table, inserted in a conspicuous location within the As-Built, with the following data. Minimum font on as-built data tables shall be 8 pts. Provide a separate fitting table for water fittings, wastewater fittings, reclaimed water fittings and chilled water fittings.
  - Fitting Number (WF#, WWF#, RF#, CF#)

- Subtype = Fitting Type (see data table file for subtypes)
- Facility Owner (JEA or PRIVATE)
- Fitting Size Primary (Inches)
- Fitting Size Secondary (Inches)
- Manufacturer
- Fitting Material (DIMJ, PVC or HDPE)
- Lining Manufacturer
- Lining Material
- Fitting Top Elevation (feet)
- Finished Grade Elevation (feet)
- Fitting Depth (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)
- IV.2.3. Fitting table shall also be submitted in excel format using the JEA standard excel file which can be downloaded from jea.com. See end of section for data table examples.

### IV.3. VALVES

- IV.3.1. Each valve shall show a call out designating valve number, valve type, and valve size with leader pointing to the installed valve. All valves should be clearly shown on the main.
- IV.3.2. Air release valves in manholes called out and shown on plan view and included in valve table.
- IV.3.3. Each valve shall be designated in a valve table, inserted in a conspicuous location within the As-Built, with the following data. Minimum font on as-built data tables shall be 8 pts. Provide a separate valve table for water valves, wastewater valves, reclaimed valves and chilled water valves.
  - Valve Number (WV#, WWV#, RV#, CV#)
  - Valve Subtype = Valve, ARV, Backflow, Hydrant (See data file for subtypes)
  - Valve Type
  - Facility Owner (JEA or PRIVATE)
  - Valve Size
  - Valve Orientation (Underground/Aboveground)
  - Valve Open Direction (left/right)
  - Valve number of turns required to open the valve
  - Valve Nut Elevation (feet)
  - Finished Grade Elevation (feet)
  - Depth to Nut (feet)
  - Valve Manufacturer

- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)
- **IV.3.4.** Valve table shall also be submitted in excel format using the JEA standard excel file which can be downloaded from jea.com. See end of section for data table examples.

### IV.4. HYDRANTS

- IV.4.1. Each hydrant shall show a call out designating hydrant number with leader pointing to the installed hydrant.
- **IV.4.2.** Each hydrant shall be designated in a hydrant table, inserted in a conspicuous location within the As-Built, with the following data. Minimum font on as-built data tables shall be 8 pts. Provide a separate hydrant table for water hydrants and reclaimed hydrants.
  - Hydrant Number (WH#, RH#)
  - Facility Owner (JEA or PRIVATE)
  - Hydrant Manufacture Date (year)
  - Hydrant Manufacturer
  - X Coord (State Plane Easting feet)
  - Y Coord (State Plane Northing feet)
  - Latitude (in Decimal Degrees)
  - Longitude (in Decimal Degrees)
  - RFID/Barcode Number
- IV.4.3. Hydrant table shall also be submitted in excel format using the JEA standard excel file which can be downloaded from jea.com. See end of section for data table examples.

## IV.5. MANHOLES

- **IV.5.1.** Each manhole shall show a call out designating manhole number, manhole type, manhole top elevation, invert elevations (with direction) with leader pointing to the installed manhole.
- **IV.5.2.** Each manhole shall be designated in a manhole table, inserted in a conspicuous location within the As-Built, with the following data. Minimum font on as-built data tables shall be 8 pts.
  - Manhole Number (MH#)
  - Manhole Subtype = Collection, Force main, Low Pressure, Trunk (See data file for subtypes)
  - Facility Owner (JEA or PRIVATE)
  - Manhole Type (A through J)
  - Manhole Drop Type (Inside or Outside)
  - Manufacturer/Supplier
  - Manhole Size (feet)

- Manhole Material
- Manhole Lining Material
- Manhole Lining Manufacturer
- · Rim Elevation (feet)
- Invert Elevations (feet) with Directions
- Lowest Invert Elevation (feet)
- Exterior Joint Tape Type
- Exterior Joint Tape Manufacturer
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)
- RFID/Barcode Number
- IV.5.3. Manhole table shall also be submitted in excel format using the JEA standard excel file which can be downloaded from jea.com. See end of section for data table examples.

## IV.6. METERS AND METER BOXES

- IV.6.1. Each meter box shall be shown on the as-built drawings. The size meter to be installed in the meter box shall also be indicated adjacent to the meter box or meter box notes. Horizontal dimensioning on the as-built is not required if meter box is located as per standards and is in a residential subdivision.
- **IV.6.2.** Each meter box shall be designated in a meter box table, inserted in a conspicuous location within the As-Built, with the following data. Minimum font on as-built data tables shall be 8 pts. Provide a separate meter box table for water and reclaimed water meter boxes.
  - Meter Box Number
  - Proposed meter size to be installed by JEA
  - Meter Subtype = Minor Meter (<2"), Major Meter, Irrigation Meter</li>
  - Facility Owner (JEA or PRIVATE)
  - Meter Box Orientation (Underground/Aboveground)
  - Meter Box Manufacturer
  - Meter Box Material
  - X Coord (State Plane Easting feet)
  - Y Coord (State Plane Northing feet)
  - Latitude (in Decimal Degrees)
  - Longitude (in Decimal Degrees)

<sup>\*\*</sup>For platted subdivisions with lot numbers on the as-builts, as-builts will not be required to identify each water meter or reclaimed meter individually at each point. The lot number combined with a meter prefix will be used to identify the customer points in the meter table.

IV.6.3. Meter box table shall also be submitted in excel format using the JEA standard excel file which can be downloaded from jea.com. See end of section for data table examples.

# IV.7. WASTEWATER SERVICE POINTS

- IV.7.1. Each wastewater service lateral end point shall be shown on the as-built drawings. Horizontal dimensioning on the as-built is not required if service point is located as per standards and is in a residential subdivision.
- **IV.7.2.** Each wastewater service points shall be designated in a wastewater service point table, inserted in a conspicuous location within the As-Built, with the following data. Minimum font on as-built data tables shall be 8 pts.
  - Wastewater Service Point Number
  - Wastewater Service Point Subtype = Customer point, Sewer Flow Meter (See data table file for subtypes)
  - Finished Grade Elevation (feet)
  - Top of Pipe Elevation (feet)
  - Depth of Cover (feet)
  - X Coord (State Plane Easting feet)
  - Y Coord (State Plane Northing feet)
  - Latitude (in Decimal Degrees)
  - Longitude (in Decimal Degrees)

IV.7.3. Wastewater service point table shall also be submitted in excel format using the JEA standard excel file which can be downloaded from jea.com. See end of section for data table examples.

## IV.8. LOCATE WIRE BOXES

- IV.8.1. Each locate wire box shall show a call out designating locate wire box number with leader pointing to the installed box.
- IV.8.2. Each locate wire box shall be designated in a locate wire box table, inserted in a conspicuous location within the As-Built, with the following data. Minimum font on as-built data tables shall be 8 pts. Provide a separate locate wire box table for water, wastewater, reclaimed water and chilled water boxes.
  - Locate Wire Box Number (WL, WWL, RL, CL)
  - Locate Box Subtype
  - X Coord (State Plane Easting feet)
  - Y Coord (State Plane Northing feet)
  - Latitude (in Decimal Degrees)
  - Longitude (in Decimal Degrees)

<sup>\*\*</sup>For platted subdivisions with lot numbers on the as-builts, as-builts will not be required to identify each wastewater connection point individually at each point. The lot number combined with a meter prefix will be used to identify the customer points in the wastewater service point and meter table.

IV.8.3. Locate wire box table shall also be submitted in excel format using the JEA standard excel file which can be downloaded from jea.com. See end of section for data table examples.

# IV.9. WASTEWATER, WATER, RECLAIMED WATER PUMPING STATIONS

Wastewater, water, and reclaimed water standard attribute worksheets shall be submitted in excel format using the JEA standard excel file which can be downloaded from jea.com.

# **IV.10. DATA TABLE EXAMPLES**

# Sample Gravity Wastewater Sewer Pipe Table:

_			
GM3	GM2	GM1	Sewer Pipe Run Number
Collection	Collection	Collection	Sewer Pipe Subtype
JEA	JEA	JEA	Facility Owner
12	8	8	Pipe Size (inches)
SDR26	SDR26	SDR26	Pipe Class
US Pipe	US Pipe	US Pipe	Pipe Manufacturer
PVC	PVC	PVC	Pipe Material
US Pipe	US Pipe	US Pipe	Pipe Lining Manufacturer
Epoxy	Epoxy	Epoxy	Pipe Lining Material
375.76	299.34	289.56	Pipe Length (feet)
23.60	24.86	26.94	Downstream Pipe Invert Elevation (feet)
33.2	32.4	32.3	Downstream Grade Elevation at Invert (feet)
24.73	26.81	28.9	Upstream Pipe Invert Elevation (feet)
32.4	32.3	32.1	Upstream Grade Elevation at Invert (feet)
0.003	0.0039	0.004	Slope (ft/ft)

# Sample Pipe Crossing Table:

CR2	CR1	Crossing Number
Potable Water	Potable Water	Upper Pipe Type
12	8	Upper Pipe Size (inches)
33.20	35.50	Finished Grade Elevation (feet)
30.20	32.10	Upper Pipe Top Elevation (feet)
3.00	3.40	Cover to Top of Upper Pipe (feet)
29.12	31.35	Upper Pipe Bottom Elevation (feet)
Force Main	Gravity Sewer	Lower Pipe Type
4	8	Lower Pipe Size (inches)
26.81	25.92	Lower Pipe Top Elevation (feet)
6.39	9.58	Cover to Top of Lower Pipe (feet)
2.30	5.43	Separation Between Pipes (feet)
455667.55	455667.55	State Plane X Coord (feet)
2193930.60	2193930.60	State Plane Y Coord (feet)
30.36691 6	30.36691 6	Latitude (Decimal Degrees)
81.778950	81.778950	Longitude (Decimal Degrees)

# Sample Water Points along Pipe Table:

WPOL2	WPOL1	WPOC1	Pipe Location Number
Top of Pipe	Top of Pipe	Point of Connection	Pipe Location
Distribution Main	Distribution Main	Distribution Main	Pipe Subtype
JEA	JEA	JEA	Facility Owner
8	8	8	Pipe Size (inches)
Aboveground	Aboveground	Underground	Pipe Orientation
PC150	PC150	DR18	Pipe Class
US Pipe	US Pipe	Diamond Plastics	Pipe Manufacturer
DI	DI	PVC	Pipe Material
US Pipe	US Pipe	N/A	Pipe Lining Manufacturer
Cement	Cement	N/A	Pipe Lining Material
23.20	23.20	23.50	Finished Grade Elevation (feet)
19.76	19.76	19.73	Pipe Top Elevation (feet)
3.44	3.44	3.77	Pipe Cover (feet)
455667.55	455667.55	455667.55	State Plane X Coord (feet)
455667,55 2193930,60	455667.55 2193930.60	455667.55 2193930.60	State Plane Y Coord (feet)
30.366916	30.366916	30.366916	Latitude (Decimal Degrees)
81.778950	81.778950	81.778950	Longitude (Decimal Degrees)

	WPOL3
elameS.	Top of Pipe
otewotseW	Distribution Main
· Points	JEA
along Pin	12
ıe Tahle∙	Underground
	DR18
	Diamond Plastics
	PVC
	N/A
	N/A
	23.10
	19.90
	3.20
	455667.55
	2193930.60
	30.366916
	81,778950

# Sample wastewater Forms along Fipe Table:

WWPOL2	WWPOL1	WWPOC2	WWPOC1	Pipe Location Number
Top of Pipe	Top of Pipe	Point of Connection	Point of Connection	Pipe Location
Force Main	Force Main	Force Main	Collection Main	Pipe Subtype
JEA	JEA	JEA	JEA	Facility Owner
12	12	8	8	Pipe Size (inches)
Underground	Underground	Underground	Underground	Pipe Orientation
DR18	DR18	DR18	SDR26	Pipe Class
Diamond Plastics	Diamond Plastics	Diamond Plastics	Diamond Plastics	Pipe Manufacturer
PVC	PVC	PVC	PVC	Pipe Material
N/A	N/A	N/A	N/A	Pipe Lining Manufacturer
N/A	N/A	N/A	N/A	Pipe Lining Material
23.1	23.1	23.2	23,5	Finished Grade Elevation (feet)
19.80	19.90	19.76	17.73	Pipe Top Elevation (feet)
3,30	3.20	3.44	5.77	Pipe Cover (feet)
455667.55	455667.55	455667.55	455667,55	State Plane X Coord (feet)
455667.55 2193930.60 30.366916	2193930.60	2193930.60 30.366916	2193930.60 30.366916	State Plane Y Coord (feet)
	30,366916			Latitude (Decimal Degrees)
81.778950	81.778950	81.778950	81.778950	Longitude (Decimal Degrees)

# Sample Reclaimed Points along Pipe Table:

RPOL2	RPOL1	RPOC1	Pipe Location Number
Top of Pipe	Top of Pipe	Point of Connection	Pipe Location
Reclaimed Main	Reclaimed Main	Reclaimed Main	Pipe Subtype
JEA	JEA	JEA	Facility Owner
12	12	8	Pipe Size (inches)
Underground	Underground	Underground	Pipe Orientation
DR18	DR18	DR18	Pipe Class
Diamond Plastics	Diamond Plastics	Diamond Plastics	Pipe Manufacturer
PVC	PVC	PVC	Pipe Material
N/A	N/A	N/A	Pipe Lining Manufacturer
N/A	N/A	N/A	Pipe Lining Material
23.1	23.1	23.5	Finished Grade Elevation (feet)
19.80	19.90	19.73	Pipe Top Elevation (feet)
3.30	3.20	3.77	Pipe Cover (feet)
455667.55	455667.55	455667.55	State Plane X Coord (feet)
2193930.60	2193930.60	2193930.60	State Plane Y Coord (feet)
30.366916	30.366916	30.366916	Latitude (Decimal Degrees)
81.778950	81.778950	81.778950	Longitude (Decimal Degrees)

# Sample Fitting Table:

WF3	WF2	WF1	Fitting Number
Reducer	Tee	Elbow 90	Fitting Subtype
Private	JEA	JEA	Facility Owner
12	8	8	Fitting Size Primary (inches)
တ	4		Fitting Size Secondary (inches)
American	American	American	Manufacturer
D	DI	DI	Fitting Material
American	American	American	Lining Manufacturer
Epoxy	Epoxy	Epoxy	Lining Material
8.4	9.4	9.4	Fitting Top Elev. (feet)
11.5	12.5	12.5	Finished Grade Elev. (feet)
<u>3.1</u>	3.1	3.1	Fitting Depth (feet)
455667.55	455667.55	455667.55	State Plane X Coord (feet)
455667.55 2193930.60 30.366916	455667.55 2193930.60 30.366916	455667.55   2193930.60   30.366916	State Plane Y Coord (feet)
30.366916		٠,	Latitude (Decimal Degrees)
-81.778950	-81.778950	-81.778950	Longitude (Decimal Degrees)

# Sample Water Valve Table:

WV2	WV1	Valve Number
Valve	Valve	Valve Subtype
Plug	Gate	Valve Type
JEA	JEA	Facility Owner
6	6	Valve Size
Underground	Underground	Valve Orientation
Right	Left	Valve Open Direction
4	18	Turns to Open
9.8	10.1	Valve Nut Elevation (feet)
12.6	12.6	Finished Grade Elevation (feet)
2.8	2.5	Depth to Nut (feet)
M&H	Clow	Valve Manufacturer
455667.55	455667.55	State Plane X Coord (feet)
2193930.60	2193930.60	State Plane Y Coord (feet)
30.366916	30.366916	Latitude (Decimal Degrees)
-81.778950	-81.778950	Longitude (Decimal Degrees)

# Sample Hydrant Table:

	-81.778950	30.366916	2193930.60	455667.55	Mueller	2017	JEA	WH3
	-81.778950	30.366916	2193930.60	455667.55	Mueller	2017	JEA	WH2
	-81.778950	30.366916	2193930.60	455667.55	Mueller	2017	JEA	WH1
RFID / Barcode Number	Longitude (Decimal Degrees)	Latitude (Decimal Degrees)	State Plane Y Coord (feet)	State Plane X Coord (feet)	Hydrant Manufacturer	Hydrant Manufacture Date (year)	Facility Owner	Hydrant Number

# Sample Manhole Table:

MH3	MH2	MH1	Manhole Number
Collection	Force main	Collection	Manhole Subtype
JEA	JEA	JEA	Facility Owner
В	Α	Þ	Manhole Type
Inside	N/A	N/A	Manhole Drop Type
Standard Precast	Standard Precast	Standard Precast	Manufacturer or Supplier
4	4	4	Manhole Size (feet)
Precast	Precast	Precast	Manhole Material
Epoxy	Spectrashield Spectrashield	Ероху	Manhole Lining Material
Spectrashield	Spectrashield	Spectrashield	Manhole Lining Manufacturer
12.6	12.2	12.9	Rim Elevation (feet)
6.23 North 8.11 South	5.88 North	6.83 North 6.90 South 6.92 SW	Invert Elevations (feet) with Directions
6.23	5.88	6.83	Lowest Invert Elevation (feet)
Joint Wrap	Joint Wrap	Joint Wrap	Exterior Joint Tape Type
Con Seal	Con Seal	Con Seal	Exterior Joint Tape Manufacturer
455667.5	455667.5	455667.5	State Plane X Coord (feet)
2193930.6	2193930.6	2193930.6	State Plane Y Coord (feet)
455667.5 2193930.6 30.366916 -81.778950	455667.5 2193930.6 30.366916 -81.778950	30.366916 -81.778950	Latitude (Decimal Degrees)
-81.778950	-81.778950	-81.778950	Longitude (Decimal Degrees)
			RFID / Barcode Number

# Sample Water Meter Box Table:

-81.778950	30.366916	2193930.60	455667.55	Concrete	Glassmasters	Underground	JEA	Minor Meter	Existing	WM3
-81.778950	30.366916	2193930.60	455667.55	Concrete	Glassmasters	Underground	JEA	Major Meter	1 1/2"	WM2
-81.778950	30.366916	2193930.60	455667.55	Polymer	Glassmasters	Underground	JEA	Minor Meter	1 ½"	WM1
Longitude (Decimal Degrees)	Latitude (Decimal Degrees)	State Plane Y Coord (feet)	State Plane X Coord (feet)	Meter Box Material	Meter Box Manufacturer/Supplier	Meter Box Orientation	Facility Owner	Meter Box Subtype	Proposed Meter Size	Meter Box Number

# Sample Wastewater Service Point Table:

		1		=1.4	. *	1000		*******
-81.778950	30.366916	2193930.60	455667.55	2.5	10.4	12.6	Customer Point	WWSP3
-81.778950	30.366916	2193930.60	455667.55	3.6	8.6	12.2	Customer Point	WWSP2
-81.778950	30.366916	2193930.60	455667.55	2.5	10.4	12.9	Customer Point	WWSP1
Longitude (Decimal Degrees)	Latitude (Decimal Degrees)	State Plane Y Coord (feet)	State Plane X Coord (feet)	Depth of Cover (feet)	Top of Pipe Elevation at Service Point (feet)	Finished Grade Elevation at Service Point (feet)	Service Point Subtype	Wastewater Service Point Number

# Sample Locate Wire Box Table:

 Locate Box Number	Locate Box Subtype	X Coord (feet)	Y Coord (feet)	Latitude (Decimal Degrees)	Longitude (Decimal Degrees)
 WL1	Locate Wire Box	455667.55	2193930.60	30.366916	-81.778950
 WL2	Locate Wire Box	455667.55	2193930.60	30.366916	-81.778950
 WL3	Locate Wire Box	455667.55	2193930.60	30.366916	-81.778950

# Sample Reclaimed Meter Box Table:

Meter Type & Lot Number	Proposed Meter Size	Meter Box Subtype	Facility Owner	Meter Box Orientation	Meter Box Manufacturer/Supplier	Meter Box Material	X Coord (feet)	Y Coord (feet)	(Decimal Degrees)	(Decimal Degrees)
RM1	1 ½"	Minor Meter	JEA	Underground	Glassmasters	Polymer	455667.55	2193930.60	30.3669169	-81 778950
RM2	1 1/2"	Minor Meter	JEA	Underground	Glassmasters	Polymer	455667.55	2193930.60	30.3669169	-81.7789500
RM3	1 1/2"	Minor Meter	JEA	Underground	Glassmasters	Polymer	455667.55	2193930.60	30.3669169	-81.778950

## V. SUBMITTAL TRANSMITTALS AND CHECKLISTS

## V.1. AS-BUILT OR RECORD DRAWING CERTIFICATION BLOCKS:

The following information (as applicable) shall be displayed on each page of the As-Built or Record drawing set. For preliminary as-built or record drawing review, all fields must be filled out including signature, date and license numbers. The seal must be supplied on the final approved as builts.

## V.1.1. FOR ENGINEERS:

AS-BUILT	
INFORMATION PROVIDED BY:	
Date:	
Name:	
Address	
Phone#:	
I HEREBY CERTIFY THAT THE	
	Chilled Water
Pavement	Water Main
Curb & Gutter	Reclaimed Water Main
Storm & Drainage System	Force Main
Lake or Pond	Sanitary Gravity System
Underdrain Connections	Lift Station
ARE AT THE HORIZONTAL AND VERTICAL LOCATIONS AS SHOTHE ACCOMPANYING ELECTRONIC FILES HAVE BEEN LOCAT CHAPTER 471 OF FLORIDA STATUTES, CHAPTER 61G15-23 O ENGINEERS AND THE JEA STANDARDS FOR AS-BUILT DRAW	ED AND MAPPED IN ACCORDANCE WITH F THE FLORIDA BOARD OF PROFESSIONAL
ELECTRONIC DRAWING FILE NAME:FILE DATE:DATE OF FIELD SURVEY	
SIGNATURE:NAME:FLORIDA PROFESSIONAL ENGINEER NO:	

## V.1.2. FOR SURVEYORS:

LAG BUILT			
AS-BUILT			
INFORMATION PROVIDED BY:			
Name:			<del>-</del>
Address:			<del>-</del>
·			-
Phone#:			-
-			-
I HEREBY CERTIFY THAT THE			
		Chilled Water	
Pavement		Water Main	
Curb & Gutter		Reclaimed Water M	lain
Storm & Draina	ge System	Force Main	
Lake or Pond		Sanitary Gravity Sys	stem
Underdrain Con	nections	Lift Station	
MEET THE- <u>MINIMUM</u> TECHNICAL PER CHAPTER 5J-17.051 AND 5J- ELECTRONIC DRAWING FILE FILE DATE:	STANDARDS FOR SURVI 17.052, F.A.C. NAME:	SHOWN ON THESE "AS-BUILT" DRA	OF FLORIDA AS
SURVEYOR'S SIGNATURE:			
SURVEYOR'S NAME:			
PSM#:			
		IPLETE WITHOUT THE OTHER AND OF THE FLORIDA LICENSED SURVE	

# V.1.3. FOR CONTRACTORS:

AS-BUILT		
INFORMATION PROVIDED BY:		
Date:		
Name:		
Address		
_		
Phone#:		
_		
I HEREBY CERTIFY THAT THE MAT	FERIALS AND QUANTITIES USE	O IN THE CONSTRUCTION OF:
		Chilled Water
Pavement		Water Main
Curb & Gutter		Reclaimed Water Main
Storm & Drainag	je System	Force Main
Lake or Pond		Sanitary Gravity System
Underdrain Con	nections	Lift Station
		ANDARDS AND COUNTY SPECIFICATIONS,
UNLESS OTHERWISE APPROVED	BY THE REGULATORY AGENCY	•
CONTRACTOR'S SIGNATURE:_		
CONTRACTOR'S NAME:		
CONTRACTOR'S STATE UTILITI	ES LICENSE NUMBER:	

# V.1.4. FOR PROJECT MANAGERS:

RECORD DRAWING		
INFORMATION PROVIDED BY:		
Date:		
Name:		
Address		
Phone#:		
- Friorie#. -		
LHERERY CERTIFY THAT THE N	MATERIALS AND QUANTITIES US	ED IN THE CONSTRUCTION OF
THEREST SERVICE THERE	WITTER WILL THE GOTHT THE OC	IN THE CONCINCOTION OF.
		Chilled Water
Pavement		Water Main
Curb & Gutter		Reclaimed Water Main
Storm & Drainag	e System	Force Main
Lake or Pond		Sanitary Gravity System
Underdrain Conr	nections	Lift Station
SPECIFICATIONS, UNLESS OTH	IE APPROVED PLANS AND JEA S' HERWISE APPROVED BY THE REI HORIZONTAL AND VERTICAL LOC	GULATORY AGENCY.
JEA PROJECT MANAGER'S SIG	NATURE:	
JEA PROJECT MANAGER'S NAM	ИЕ:	

# V.2. JEA AS-BUILT OR RECORD DRAWING SUBMITTAL TRANSMITTAL

Water / Wastewater / Reclaimed Water / Chilled Water Pipes and Pumping

To:	W&S As-Built Submittal	Mailbox		
From:				
Phone:		E-mail:		
Company Name:				
Company Address				
Date of Submittal:				
Signature of Submitter Verifying Compliance:				
Project Name:				
Project Type: (Check all that apply)	New Development	Treatment Plant	JEA Installed	JEA Contractor
Project Purpose	Main Extension	Main Replacement	Main Relocation	Plant Project
JEA Availability Number:			JEA Capital Project Number:	
JEA Project Manager:			JEA PM e-mail:	
Engineering Firm:				
Engineering Contact:				
Engineers Phone:				
Engineers E-mail:				
Contracting Co.:				
Contractor Contact:				
Contractor Phone:				
Contractor E-Mail:				
Surveying Co.:				
Surveyor Contact:				
Surveyors Phone:				
Surveyors E-mail:				
JEA O&M representative:				
Attached:	Water As-Builts & [	Data Tables – Electronic		
		ilts & Data Tables – Elect		
		Station Attribute Tables E		
		As-Builts & Data Tables –		
		uilts & Data Tables – Elec		
		Checklist filled out by Eng Checklist filled out by JEA	lineer, Contractor or Surve	eyor
		e Worksheets completed	r i Toject Managei	
	Equipment / turbut	c		

# V.3. JEA AS-BUILT OR RECORD DRAWING SUBMITTAL REQUIREMENTS CHECK LIST PIPELINES AND PUMPING STATIONS

Project Name:	
JEA Availability Number:	JEA Capital Project Number:
	Initial next to each requirement verifying compliance
Separate As-Builts or r	ecord drawings for water, wastewater, reclaimed water and chilled water
On each page of as-bu	ilt, certification filled out, signed, sealed and dated by surveyor/mapper
On each page of as-bu	ilt, certification filled out, signed and dated by contractor
On each page of record	d drawing, certification filled out, signed and dated by JEA project manager
Old lines not built as pe	er design deleted and redrawn as constructed
Notes and elevations n	ot struck through, but changed
"AS-BUILT" or "RECOF	RD DRAWING" labeled in 1" letters on each page
PDF sheets are 24" x 3	86" in size
All PDF sheets combin	ed into one document
All Utility Services (Wa	ter/Sewer/Reclaimed/Chilled) provided on first and every submittal
CAD and Excel files pro	ovided on first and every submittal
Includes all changes by	Addendum or Change Order or SWA (Supplemental Work Allowance)
As-Built Includes datun	n & reference to state plane coordinates (Florida East Zone NAD 83, NAVD 88)
Vicinity map on cover p	page
Street names on all stre	eets
North Arrow and Graph	nic Scale on each page
Cover Page required w	rhich is a separate page from Utility Pages
Call outs provided for a	any main that is Removed, Abandoned/Grout Filled, or Out of Service. Call out beginning and end points
Availability number and	d/or JEA Capital Project number on Cover Page and on each page
JEA easements labeled	d as such, including RE number and Official Records Book and Page (OR #).
Date of utility installatio	on completion on Cover Page
Ownership transition po	pint between JEA and Private system clearly designated on the as-built drawing.
Master Plan showing p	hasing for the entire development
Match lines shown for o	continuation to other sheets

Private utilities installed as part of this project shown
Call outs provided showing points of connection to existing JEA infrastructure.
Water pressure and/or force main pressure sensors are identified.
Pump station as built include all detail sheets.
As Built Cover Page
Title with "As-Built" and Project Name underneath. If known, provide address
Availability Number and/or the JEA Capital Project Number
Vicinity Map (refer to Standards Manual for Vicinity Map requirements)
Date of utility installation completion
Legend
Surveyor Notes (includes vertical and horizontal datum)
General Notes (specific utility notes provided on utility sheets)
Certifications filled out, signed, and sealed on every sheet, including cover sheet
Title Block
Surveyor logo and address
Cover Page should not include:
As-Built utility plans
Data Tables

# POTABLE WATER SYSTEMS WATER MAINS Elevations on the main and finished grade shown at: Points of connection to the existing system and called out on the plan view and shown in the points along pipe table In the event of potable water temporarily serving irrigation demand, call out the point of connection between potable and reclaimed Points of crossing over or under wastewater mains, reclaimed mains, chilled water mains or storm drains called out on the plan view and shown in the pipe crossing table At maximum of 100 ft. intervals called out on the plan view and shown in the points along pipe table Where less than 30 inches or greater than 48 inches of cover is provided called out on the plan view and shown in the points along pipe table Main stub outs called out on the plan view and shown in the points along pipe table Beginning and ending points of pipe exposed aboveground are shown in the points along pipe table, with Pipe Orientation noted as Aboveground Each water main section is shown with pipe size, pipe material and pipe pressure class called out with a leader line pointing to the applicable main. A new call out should be placed when the pipe size changes. Provide a note on each water sheet for water service laterals stating the size, pressure class, and material Beginning and end points of horizontal directional drills located by professional surveyor HDD (Horizontal directional drill) bore log included showing: Bore in plan view showing length and beginning/end points called out with coordinates Bore profile view provided on separate sheet Bore log on 24" x 36" sheets Certified by HDD contractor Horizontal and vertical location data at 25 ft. intervals (max) Points along Pipe table with data at points of connection and maximum 100 ft intervals: Pipe Location Number (WPOC#, WWPOL#, etc) Pipe Location (Point of Connection, Top of Pipe, Top of Casing)

- Pipe Subtype
- Facility Owner
- Pipe Size
- Pipe Orientation
- Pipe Class
- Pipe Manufacturer
- Pipe Material
- Pipe Lining Manufacturer
- Pipe Lining Material

- Finished Grade Elevation (feet)
- Pipe Top Elevation (feet)
- Pipe Cover (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (Decimal Degrees)
- Longitude (Decimal Degrees)

Pipe Crossing table with data at each crossing:

- Crossing Number
- Upper Pipe Type
- Upper Pipe Size
- Finished Grade Elevation (feet)
- Upper Pipe Top Elevation (feet)
- Cover to Top of Upper Pipe (feet)
- Upper Pipe Bottom Elevation (feet)
- Lower Pipe Type
- Lower Pipe Size (inches)
- Lower Pipe Top Elevation (feet)
- Cover to Top of Lower Pipe (feet)
- Separation Between Pipes (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (Decimal Degrees)
- Longitude (Decimal Degrees)

## **WATER FITTINGS**

Each fitting shows a call out designating fitting number, fitting type (45, tee, etc.) and size with leader pointing to the installed fitting. All Fittings should be clearly shown on the main.

Table included with data for each fitting:

- Fitting Number (WF#)
- Subtype = Fitting Type (see data table file for subtypes)
- Facility Owner (JEA or PRIVATE)
- Fitting Size Primary (Inches)
- Fitting Size Secondary (Inches)
- Manufacturer
- Fitting Material (DIMJ, PVC or HDPE)
- Lining Manufacturer
- Lining Material
- Fitting Top Elevation (feet)
- Finished Grade Elevation (feet)
- Fitting Depth (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

### **WATER VALVES**

Each valve shows a call out designating valve number, valve type, and valve size with leader pointing to the installed valve. All Valves should be clearly shown on the main.

Table included with data for each valve:

- Valve Number (WV#)
- Valve Subtype = Valve, ARV, Backflow, Hydrant
- Valve Type
- Facility Owner (JEA or PRIVATE)
- Valve Size
- Valve Orientation
- Valve Open Direction (left/right)
- Valve number of turns required to open the valve
- Valve Nut Elevation (feet)
- Finished Grade Elevation (feet)
- Depth to Nut (feet)
- Valve Manufacturer
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

## **WATER HYDRANTS**

Each hydrant shows a call out designating hydrant number with leader pointing to the installed hydrant.

Table included with data for each hydrant:

- Hydrant Number (WH#)
- Facility Owner (JEA or PRIVATE)
- Hydrant Manufacture Date (year)
- Hydrant Manufacturer
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)
- RFID/Barcode Number

## **WATER METERS AND METER BOXES**

Each meter box shall be listed in the data table with meter number matching the Lot # or Address #. If no Lot # or Address # exists, assign a water meter number not included in the Lot # series. Show this meter number at the meter on the plan view and in the data table.

Irrigation Meters shall be numbered with Meter Number, shown and called out on the plan view and included in the water meter data table.

Location of meter boxes indicated and referenced to property lines (not necessary for 2 inch or less residential meters located as per standards).

The size meter to be installed for each meter

Table included with data for each water meter box:

- Meter Box Number (WM#)
- Proposed Meter Size
- Meter Subtype = Minor Meter (<2"), Major Meter, Irrigation Meter
- Facility Owner (JEA or PRIVATE)
- Meter Box Orientation
- Meter Box Manufacturer
- Meter Box Material
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

# **WATER LOCATE WIRE BOXES**

Each locate wire box shows a call out designating locate wire box number with leader pointing to the installed box
Table included with data for each locate wire box:

- Locate Wire Box Number (WL#)
- Locate Box Subtype (Marker Ball, Locate Wire Box)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

# **WASTEWATER SYSTEMS**

<b>GRAVITY M</b>	<u>AINS</u>
Elevat	tions on the main and finished grade shown at:
•	Points of connection to the existing system and called out on the plan view and shown in the points along pipe table Points of crossing over or under water mains, reclaimed mains, chilled water mains, wastewater mains or storm drains and shown in the pipe crossing table Lateral (service) end points Main stub outs
-	ning and ending points of pipe exposed aboveground are shown in the points along pipe table, with Orientation noted as Aboveground.
Vertica	al separation called out at crossings with water mains
Plan a	and profile drawings provided showing pipe and manholes
	gravity wastewater main section between manholes is shown with pipe size, pipe material, pipe ure class, pipe length and slope called out with a leader line pointing to the applicable main.
Call o	ut High Line (HL) and Low Line (LL) on the plan and profile view
Note it	f Sewer Service ties into Low Line in profile view
Provid	le a note on each sewer sheet for sewer laterals stating the size, pressure class, and material
The lo	cation of the service point for each lateral located from the side property line or by station and
Table	included with data for each gravity main:
	Sewer Pipe Run Number (GM#) Sewer Pipe Subtype = Collection, Trunk Facility Owner (JEA or PRIVATE) Pipe Size (Inches) Pipe Class (SDR26, etc.) Pipe Material (PVC, etc.) Pipe Manufacturer Pipe Length (feet) Downstream Pipe Invert Elevation (feet) Downstream Grade Elevation at Invert (feet) Upstream Pipe Invert Elevation (feet) Upstream Grade Elevation at Invert (feet)

Slope (feet/feet)

## **GRAVITY FITTINGS**

Each fitting shows a call out designating fitting number, fitting type (cleanout, wye, plug, etc) and size with leader pointing to the installed fitting. All fittings shall be clearly shown on the main.

Table included with data for each fitting:

- Fitting Number (WWF#)
- Subtype = Fitting Type (see data table file for subtypes)
- Facility Owner (JEA or PRIVATE)
- Fitting Size Primary (Inches)
- Fitting Size Secondary (Inches)
- Manufacturer
- Fitting Material (DI, PVC or HDPE)
- Lining Manufacturer
- Lining Material
- Fitting Top Elevation (feet)
- Finished Grade Elevation (feet)
- Fitting Depth (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

#### **MANHOLES**

Manholes labeled with manhole number and called out with manhole type, rim elevation, and invert elevations with a leader pointing to the applicable manhole.

Table with the following data for each manhole:

- Manhole Number (MH#)
- Manhole Subtype = Collection, Force main, Low Pressure, Trunk, ARV
- Facility Owner (JEA or PRIVATE)
- Manhole Type (A through J)
- Manhole Drop Type (Inside or Outside)
- Manufacturer/Supplier
- Manhole Size (feet)
- Manhole Material
- Manhole Lining Material
- Manhole Lining Manufacturer
- Rim Elevation (feet)
- Invert Elevations (feet) with Directions
- Lowest Invert Elevation (feet)
- Exterior Joint Tape Type
- Exterior Joint Tape Manufacturer
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)
- RFID/Barcode Number (future)

### **WASTEWATER SERVICE POINTS**

Each service point (sewer lateral end point) shall be listed in the data table with service point number matching the Lot # or Address #. If no Lot # or Address # exists, assign a service point number not included in the Lot # series. Show this service point number at the service point on the plan view and in the data table.

Table included with data for each wastewater service point:

- Wastewater Service Point Number (WWSP# or WWM#)
- Wastewater Service Point Subtype = Customer point, Sewer Flow Meter
- Finished Grade Elevation (feet)
- Top of Pipe Elevation (feet)
- Depth of Cover (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

#### **WASTEWATER PRESSURE MAINS**

Elevations on the main and finished grade shown at:

- Points of connection to the existing system and called out on the plan view and shown in the points along pipe table
- Points of crossing over or under water mains, reclaimed mains, chilled water mains, wastewater mains or storm drains called out on the plan view and shown in the pipe crossing table
- At maximum of 100 ft. intervals called out on the plan view and shown in the points along pipe table
- Where less than 30 inches or greater than 48 inches of cover is provided called out on the plan view and shown in the points along pipe table
- Main stub-outs

Beginning and ending points of pipe exposed aboveground are shown in the points along pipe table, with Pipe Orientation noted as Aboveground.

Each main section is shown with pipe size, pipe material and pipe pressure class called out with a leader line pointing to the applicable main. A new call out should be placed when the pipe size changes.

\_\_\_Beginning and end points of HDD (horizontal directional drills) located by professional surveyor

\_\_\_\_\_ HDD bore log included showing:

- Bore in plan view showing length and beginning/end points called out with coordinates
- Bore profile view provided on separate sheet
- Bore log on 24" x 36" sheets
- Certified by HDD contractor
- Horizontal and vertical location data continuous or at no more than 25 ft. intervals

Points along Pipe table with data at points of connection and maximum 100 ft intervals:

- Pipe Location Number
- Pipe Location (Point of Connection, Top of Pipe, Top of Casing)
- Pipe Subtype
- Facility Owner
- Pipe Size (inches)
- Pipe Orientation
- Pipe Class
- Pipe Manufacturer
- Pipe Material
- Pipe Lining Manufacturer
- Pipe Lining Material
- Finished Grade Elevation (feet)
- Pipe Top Elevation (feet)
- Pipe Cover (feet)
- X Coord (State Plane Easting feet)

- Y Coord (State Plane Northing feet)
- Latitude (Decimal Degrees)
- Longitude (Decimal Degrees)

Pipe Crossing table with data at each crossing:

- Crossing Number
- Upper Pipe Type
- Upper Pipe Size (inches)
- Finished Grade Elevation (feet)
- Upper Pipe Top Elevation (feet)
- Cover to Top of Upper Pipe (feet)
- Upper Pipe Bottom Elevation (feet)
- Lower Pipe Type
- Lower Pipe Size (inches)
- Lower Pipe Top Elevation (feet)
- Cover to Top of Lower Pipe (feet)
- Separation Between Pipes (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (Decimal Degrees)
- Longitude (Decimal Degrees)

### **FORCE MAIN FITTINGS**

Each fitting shows a call out designating fitting number, fitting type (45, tee, etc.) and size with leader pointir to the installed fitting. All Fittings should be clearly shown on the main.

Table included with data for each fitting:

- Fitting Number (FMF#)
- Subtype = Fitting Type (see data table file for subtypes)
- Facility Owner (JEA or PRIVATE)
- Fitting Size Primary (Inches)
- Fitting Size Secondary (Inches)
- Manufacturer
- Fitting Material (DI, PVC or HDPE)
- Lining Manufacturer
- Lining Material
- Fitting Top Elevation (feet)
- Finished Grade Elevation (feet)
- Fitting Depth (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

### **WASTEWATER VALVES**

Each valve shows a call out designating valve number, valve type, and valve size with leader pointing to the installed valve. All Valves should be clearly shown on the main.

Air release valves in manholes called out and shown on plan view and included in valve table.

Table included with data for each valve:

- Valve Number (WWV#)
- Valve Subtype = Valve, ARV (See data table file for subtypes)
- Valve Type
- Facility Owner (JEA or PRIVATE)
- Valve Size
- Valve Orientation
- Valve Open Direction (left/right)
- Valve number of turns required to open the valve
- Valve Nut Elevation (feet)
- Finished Grade Elevation (feet)
- Depth to Nut (feet)
- Valve Manufacturer
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

### **WASTEWATER LOCATE WIRE BOXES**

Each locate wire box shows a call out designating locate wire box number with leader pointing to the installed box

Table included with data for each locate wire box:

- Locate Wire Box Number (WWL#)
- Locate Box Subtype (Marker Ball, Locate Wire Box)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

## **WASTEWATER PUMPING STATIONS**

 Pump Station sheet is digital (not scanned and marked up) and legible when zoomed in.
 All As-Built changes are marked with AB and clouded. Corrected in AUTOCAD file, not crossed out with the new numbers.
 All pump station data/information is included on first sheet and the station layout with measurements, elevations and GPS coordinates on second sheet.
All utilities within the pump station site are located relative to property lines.
 Elevations (*and GPS coordinates) indicated at:
<ul> <li>Invert(s)</li> <li>Wet well Top (rim elevation) *</li> <li>Wet well bottom</li> <li>Concrete slab station corners</li> <li>Underground piping, valves* and fittings*</li> </ul>
Measurements of panels & equipment relative to the concrete edges of station at:
<ul> <li>Control Panel Rack</li> <li>Power Distribution Rack</li> <li>Demarcation Box(s)</li> <li>Flow Meter Panel</li> </ul>
All above and below ground piping is shown
 Wet Well shown and dimensioned from property lines
Generator/Pony pump shown and information filled out
 Driveway shown and dimensioned from property lines
 All materials, sizes of lines and fittings associated with pump station are indicated on drawings.
All buried electrical conduit shall be shown, with size indicated, including electrical service from utility transformer to station meter and to control panel.
Pump information has been checked for completeness and accuracy
 MCC Panel chart is filled out.
 Schedule of elevation chart is filled out entirely.
 Station physical address is indicated in Pump Station Information box.
Privately owned pump stations will provide pump model info for modeling purposes.
Water pressure and/or force main pressure sensors are identified.

#### RECLAIMED WATER SYSTEMS

#### **RECLAIMED WATER MAINS**

Elevations on the main and finished grade shown at:

- Points of connection to the existing system and called out on the plan view and shown in the points along pipe table
- In the event of potable water temporarily serving irrigation demand, call out the point of connection between potable and reclaimed
- Points of crossing over or under water mains, reclaimed mains, chilled water mains, wastewater mains or storm drains called out on the plan view and shown in the pipe crossing table
- At maximum of 100 ft. intervals called out on the plan view and shown in the points along pipe table
- Where less than 30 inches or greater than 48 inches of cover is provided called out on the plan view and shown in the points along pipe table
- Main stub-outs

Beginning and ending points of pipe exposed aboveground are shown in the points along pipe table, with Pipe Orientation noted as Aboveground.

Each reclaimed water main section is shown with pipe size, pipe material and pipe pressure class called out with a leader line pointing to the applicable. A new call out should be placed when the pipe size changes.

Provide a note on each water sheet for water service laterals stating the size, pressure class, and material.

Location of reclaim signage indicating reclaim water in use

Location of meter boxes indicated and referenced to property lines (not necessary for 2 inch or less residential meters located as per standards).

Beginning and end points of horizontal directional drills located by professional surveyor

HDD (Horizontal directional drill) bore log included showing:

- Bore in plan view showing length and beginning/end points called out with coordinates
- Bore profile view provided on separate sheet
- Bore log on 24" x 36" sheets
- Certified by HDD contractor
- Horizontal and vertical location data at 25 ft. intervals (max)

Points along Pipe table with data at points of connection and maximum 100 ft intervals:

- Pipe Location Number
- Pipe Location (Point of Connection, Top of Pipe, Top of Casing)
- Pipe Subtype
- Facility Owner
- Pipe Size (inches)
- Pipe Orientation
- Pipe Class
- Pipe Manufacturer
- Pipe Material
- Pipe Lining Manufacturer

- Pipe Lining Material
- Finished Grade Elevation (feet)
- Pipe Top Elevation (feet)
- Pipe Cover (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (Decimal Degrees)
- Longitude (Decimal Degrees)

Pipe Crossing table with data at each crossing:

- Crossing Number
- Upper Pipe Type
- Upper Pipe Size (inches)
- Finished Grade Elevation (feet)
- Upper Pipe Top Elevation (feet)
- Cover to Top of Pipe (feet)Upper Pipe Bottom Elevation (feet)
- Lower Pipe Type
- Lower Pipe Size (inches)
- Lower Pipe Top Elevation (feet)
- Cover to Top of Lower Pipe (feet)
- Separation Between Pipes (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (Decimal Degrees)
- Longitude (Decimal Degrees)

### **RECLAIMED WATER FITTINGS**

Each fitting shows a call out designating fitting number, fitting type (45, tee, etc.) and size with leader pointing to the installed fitting. All Fittings should be clearly shown on the main.

Table included with data for each fitting:

- Fitting Number (RF#)
- Subtype = Fitting Type (see data table file for subtypes)
- Facility Owner (JEA or PRIVATE)
- Fitting Size Primary (Inches)
- Fitting Size Secondary (Inches)
- Manufacturer
- Fitting Material (DI, PVC or HDPE)
- Lining Manufacturer
- Lining Material
- Fitting Top Elevation (feet)
- Finished Grade Elevation (feet)
- Fitting Depth (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

#### **RECLAIMED WATER VALVES**

Each valve shows a call out designating valve number, valve type, and valve size with leader pointing to the installed valve. All Valves should be clearly shown on the main.

Table included with data for each valve:

- Valve Number (RV#)
- Valve Subtype = Valve, ARV, Backflow, Flushing Hydrant (See data table file for subtypes)
- Valve Type
- Facility Owner (JEA or PRIVATE)
- Valve Size
- Valve Orientation
- Valve Open Direction (left/right)
- Valve number of turns required to open the valve
- Valve Nut Elevation (feet)
- Finished Grade Elevation (feet)
- Depth to Nut (feet)
- Valve Manufacturer
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

RECLAIMED	WATER	HYDR	ANTS
-----------	-------	------	------

Each hydrant shows a call out designating hydrant number with leader pointing to the installed hydrant.

Table included with data for each hydrant:

- Hydrant Number (RH#)
- Facility Owner (JEA or PRIVATE)
- Hydrant Manufacture Date (year)
- Hydrant Manufacturer
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)
- RFID/Barcode Number

### RECLAIMED WATER METER BOXES

Each meter box shall be listed in the data table with meter number matching the Lot # or Address #. If no Lot # or Address # exists, assign a reclaimed water meter number not included in the Lot # series. Show this meter number at the meter on the plan view and in the data table.

The size meter to be installed for each meter

Table included with data for each meter box:

- Meter Box Number (RM#)
- Proposed Meter Size
- Meter Subtype = Minor Meter (<2"), Major Meter</li>
- Facility Owner (JEA or PRIVATE)
- Meter Box Orientation
- Meter Box Manufacturer
- Meter Box Material
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

### **RECLAIMED WATER LOCATE WIRE BOXES**

Each locate wire box shows a call out designating locate wire box number with leader pointing to the installed box

Table included with data for each locate wire box:

- Locate Wire Box Number (RL#)
- Locate Box Subtype (Marker Ball, Locate Wire Box)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

### **CHILLED WATER SYSTEMS**

### **CHILLED WATER MAINS**

Elevations on the main and finished grade shown at:

- Points of connection to the existing system and called out on the plan view and shown in the points along pipe table
- Points of crossing over or under water mains, reclaimed mains, chilled water mains, wastewater mains or storm drains called out on the plan view and shown in the pipe crossing table
- At maximum of 100 ft. intervals called out on the plan view and shown in the points along pipe table
- Where less than 30 inches or greater than 48 inches of cover is provided called out on the plan view and shown in the points along pipe table

Beginning and ending points of pipe exposed aboveground are shown in the points along pipe table, with Pipe Orientation noted as Aboveground.

Each chilled water main section is shown with pipe size, pipe material and pipe pressure class called out with a leader line pointing to the applicable main. A new call out should be placed when the pipe size changes.
Each pipe labeled as to supply water or return water
Provide a note on each water sheet for water service laterals stating the size, pressure class, and material

Location of lateral end points indicated and referenced to property lines.

Beginning and end points of horizontal directional drills located by professional surveyor

HDD (Horizontal directional drill) bore log included showing:

- Bore in plan view showing length and beginning/end points called out with coordinates
- Bore profile view provided on separate sheet
- Bore log on 24" x 36" sheets
- Certified by HDD contractor
- Horizontal and vertical location data at 25 ft. intervals (max)

Points along Pipe table with data at points of connection and maximum 100 ft intervals:

- Pipe Location Number
- Pipe Location (Point of Connection, Top of Pipe, Top of Casing)
- Facility Owner
- Pipe Size (inches)
- Pipe Orientation
- Pipe Class
- Pipe Manufacturer
- Pipe Material
- Pipe Lining Manufacturer
- Pipe Lining Material
- Finished Grade Elevation (feet)
- Pipe Top Elevation (feet)

- Pipe Cover (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (Decimal Degrees)
- Longitude (Decimal Degrees)

Pipe Crossing table with data at each crossing:

- Crossing Number
- Upper Pipe Type
- Upper Pipe Size (inches)
- Finished Grade Elevation (feet)
- Upper Pipe Top Elevation (feet)
- Cover to Top of Upper Pipe (feet)
- Upper Pipe Bottom Elevation (feet)
- Lower Pipe Type
- Lower Pipe Size (inches)
- Lower Pipe Top Elevation (feet)
- Cover to Top of Lower Pipe (feet)
- Separation Between Pipes (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (Decimal Degrees)
- Longitude (Decimal Degrees)

### **CHILLED WATER FITTINGS**

Each fitting shows a call out designating fitting number, fitting type (45, tee, etc.) and size with leader
pointing to the installed fitting. All Fitting should be clearly shown on the main.
Table included with data for each fitting:

- Fitting Number (CF#)
- Subtype = Fitting Type (see data table file for subtypes)
- Facility Owner (JEA or PRIVATE)
- Fitting Size Primary (Inches)
- Fitting Size Secondary (Inches)
- Manufacturer
- Fitting Material (DI, PVC or HDPE)
- Lining Manufacturer
- Lining Material
- Fitting Top Elevation (feet)
- Finished Grade Elevation (feet)
- Fitting Depth (feet)
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

### **CHILLED WATER VALVES**

Each valve shows a call out designating valve number, valve type, and valve size with leader pointing to the installed valve. All Valves should be clearly shown on the main.

Table included with data for each valve:

- Valve Number (CV#)
- Valve Type
- Facility Owner (JEA or PRIVATE)
- Valve Size
- Valve Orientation
- Valve Open Direction (left/right)
- Valve number of turns required to open the valve
- Valve Nut Elevation (feet)
- Finished Grade Elevation (feet)
- Depth to Nut (feet)
- Valve Manufacturer
- X Coord (State Plane Easting feet)
- Y Coord (State Plane Northing feet)
- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

### **CHILLED WATER LOCATE WIRE BOXES**

Each locate wire box shows a call out designating locate wire box number with leader pointing to
the installed box
Table included with data for each locate wire box:

- Locate Wire Box Number (CL#)
  - Locate Box Subtype (Marker Ball, Locate Wire Box)
  - X Coord (State Plane Easting feet)
  - Y Coord (State Plane Northing feet)

Longitude (in Decimal Degrees)

- Latitude (in Decimal Degrees)
- Longitude (in Decimal Degrees)

### **CHILLED WATER METER ROOMS**

Each meter room shall be listed in the data table with meter number matching the Lot # or Address #. no Lot # or Address # exists, assign a chilled water meter number not included in the Lot # series. Show this meter number at the meter on the plan view and in the data table.
The size meter to be installed for each meter
Table included with data for each meter room:
<ul> <li>Meter Room Number (CM#)</li> <li>Proposed Meter Size</li> <li>Facility Owner (JEA or PRIVATE)</li> <li>X Coord (State Plane Easting feet)</li> <li>Y Coord (State Plane Northing feet)</li> <li>Latitude (in Decimal Degrees)</li> </ul>

## STORM DRAIN SYSTEMS STORM DRAIN

Runs of storm wastewaters identified with size, material and slope (i.e., 300' of 15" RCP at S=.004)

Elevations given for the north rim of the top of all manhole covers and inlets and catch basins and all manhole, inlet and catch basin inverts

All storm drain manholes, inlets and catch basin types identified

## V.4. INSPECTION CHECKLIST: LOCATE WIRE BOXES

Project Name:						
Street/Intersection/Address Location: _						
Station:         Offset:						
Check the following as applicable						
Water Wastewater Reclaimed						
Location:		Paved Area Grassed Area				
Cover at Finish Grade:		Cover at finish grade Cover above/below finish grade-adjust per spec.				
Locate wire accessible in box:		Yes No, full of debris – excavate debris				
Locate wire properly color coded:		Yes No—replace per spec				
Locate wire signal verified:		Yes No—repair per spec				
Comments:						
Contractor Representative:						
JEA Inspector:	Signature	Print name				
JEA O&M representative:	Signature	Print name				
	Signature	Print name				
Commissioned this date:						

### V.5. JEA TRACER WIRE CERTIFICATION FORM

Project Name/Number:								
Date(s) Tested:								
Installed by Contractor:								
Name of	Tester:							
Testing C	ompany:							
JEA Inspe	ector:	_						
Pass:								
Fail:								
Continuit	/Cianal atra	anath hatusan as	oooo nointo:		Ma	orkor Palla Ina	tallad / Lagats	ad.
•	⊭1 to acce	ength between ac ss pt #2:	cess points:		Marker Balls Installed / Located Color is for the utility type of Marker			
•	#3 to acce	•			Installed		Located	
•	:#5 to acce	•			Installed		Located	
Access pt	:#7 to acce	ss pt #8:			Installed		Located	
Access pt	:#9 to acce	ss pt #10:			Installed		Located	
Total	V	Vater	Sewer /	/ FM	Reclaime	ed Water	Fiber C	Optic
footage tested								
	ts found Lis	st below (please i	ndicate utility	type and loc	ation)			
Fault # 1:								
Fault # 2:								
Fault # 3:								
Fault # 4:								
Foult # 5:								
Fault # 5:								

## V.6. JEA RECORD DRAWING SUBMITTAL TRANSMITTAL

Water/ Wastewater/Reclaimed Treatment Plants, Wells and Facilities

To:	W&S As-Built Submittal Mailbox
From:	
Phone:	
E-mail:	
Company Name:	
Date of Submittal:	
Signature of	
Submitter Verifying	
Compliance:	
Drainat Nama	
Project Name:	
Project Numbers:	
JEA Project Manager: JEA PM E-mail:	
JLA FIVI L-IIIaII.	
Engineering Firm:	
Engineering Contact:	
Engineers Phone:	
Engineers E-mail:	
Contracting Co.:	
Contractor Contact:	
Contractor Phone:	
Contractor E-Mail:	
Surveying Co.:	
Surveyor Contact:	
Surveyors Phone:	
Surveyors E-mail:	
Attached:	As-Builts - Paper Copy & Electronic
	Record Drawing Submittal Checklist filled out by Engineer, Contractor or Surveyor
	Record Drawing Submittal Checklist filled out by JEA Project Manager
	Equipment Attribute Worksheets completed

## V.7. JEA RECORD DRAWING SUBMITTAL REQUIREMENTS CHECK LIST

**Treatment Plants** 

Project Name:
Project Numbers:
Initial next to each requirement verifying compliance
On each page of record drawing, certification filled out, signed and dated by the project manager
Improvements not built as per design are redrawn as constructed
"RECORD DRAWING" labeled in 1" letters on each sheet
Sheets are 24" x 36" in size
Includes all changes by Addendum or SWA (Supplemental Work Allowance), or Change Order
Includes datum & reference to state plane coordinates (Florida East Zone NAD 83, NAVD 88)
Vicinity map on cover page
Title page and each page includes JEA Oracle Project Number(s)
Provide paper and electronic copies of Record Drawing (.dwg and .pdf formats)
Street names on all streets
North Arrow on each page
Graphic Scale on each page
JEA Capital Project number on each page
JEA easements labeled as such, including RE number and Official Records Book and Page (OR #).
Date of utility installation completion on each page
PLANT INFRASTRUCTURE
Provide and incorporate into record drawings the horizontal and vertical record locations of improvements, including the following:
Corner coordinates of rectangular or square buildings, structures, and tanks.
Center coordinates of circular buildings, structures, and tanks.
Building floor elevations.
Floor elevations of structures and tanks as required to define floor slope.
Top elevations of structures and tanks and weirs.

 -
 Channel floor elevations at each change in slope.
 Channel top elevations.
 Manhole center coordinates for electrical duct banks, sanitary sewer, storm sewer, etc.
 Pipe coordinates at changes in direction.
 Coordinates of all buried valves, and fittings.
 All underground piping invert or centerline elevations.
 All underground pipe invert or centerline elevations at fittings.
 Pipe invert, or centerline, elevations at crossing with another pipe.
 Invert or top of pipe elevations and coordinates of existing pipe at crossing with new underground pipe showing Separations
Invert elevations of manhole pipe inlets and outlets.
Duct bank, storm sewer, sanitary sewer coordinates and elevations at changes in direction or offset measurements from existing Structures or Roadways.
Top and bottom elevations of duct banks at manholes and hand holes showing ID numbers
 Other horizontal and vertical record data pertinent to completed Work.
Location of internal utilities and appurtenances concealed in the construction Referenced to Structure or Roadway off set dimensions
 Details not indicated on the original contract drawings
 Depths of various elements of foundations in relation to finish first floor elevations
 Location, elevation, and datum of Benchmark used.
 Elevation of all Pump and Housekeeping Pads
 Weir Elevations
 Field changes of dimensions and or details as relates to; but not limited the following:
<ul> <li>Interior equipment</li> <li>Architectural and structural changes, including relocation of doors, windows, etc.</li> <li>Architectural schedule changes</li> </ul>
 Hydraulic profile sheetupdate control elevations and liquid elevations for low flow, average flow, and peak hourly flow conditions including return flows (as required based on equipment selection or field changes)
 Runs of storm sewers identified with size, material and slope (i.e., 300' of 15" RCP at S=.004)
Ground surface record/information shall include the following:
• Spot elevations should be shown at a minimum 100-foot rectangular grid, sufficient to show all the important topographic features

record drawing markups if finished elevations are different.

All elevations shown on the construction drawings shall be confirmed or amended on the

WELL INFRASTRUCTURE
<u>WELLS</u>
Elevation of top casing and at grade
Depth of casing below land surface
Diameter, material and thickness of casing(s)
Depth of well below land surface
Location of well, in latitude and longitude
<u>WELLHEAD</u>
Wellhead pad finished elevation
All materials and sizes of lines and fittings indicated on drawings
All buried electrical conduit labeled and located
Pipe coordinates at changes in direction
Coordinates of buried valves, tees and fittings
Other horizontal and vertical record data pertinent to completed Work
Location of internal utilities and appurtenances concealed in the construction referenced to visible accessiblefeatures
Field changes of dimensions and or details
Location, elevation, and datum of Benchmark used

Blank Page